Printing date 03.01.2020

Version: 6

Revision: 03.01.2020

1.1 Product identifier	
U	DUSE NEW (Listed NSF A8: n° 152106)
Article number: 0282000 1.2 Relevant identified us Sector of Use SU22 Pro	n Sees of the substance or mixture and uses advised against fessional uses: Public domain (administration, education, entertainment, services, craftsmen) Washing and cleaning products (including solvent based products) ing
	nce / the mixture Cleaning material/ Detergent
1.3 Details of the supplie Manufacturer/Supplier: ZEP UK Ltd Tanhouse Lane Widnes Cheshire, WA8 01 United Kingdom Tel: +44 (0)151 422 1000 Fax: +44 (0)151 422 101 @: info@zep.co.uk web: www.zep.co.uk	RD D
ZEP Industries BV Vierlinghweg 30 4612 PN Bergen op Zoon The Netherlands Tel: (NL) + 31 164 250 1 Fax:(NL) + 31 164 266 7 @: sales@zepbenelux.com	00 (B) + 32 2 347 0117 10 (B) + 32 2 347 1395
ZEP ITALIA SRL Via Netunese Km. 25.000 04011 Aprilia (LT) - Italy Tel: +39.06.926691 Fax: +39.06.92747061 @: tecnico@zepeurope.co Sito: www.zep.it	,
B: Tel: +32 2 347 0117 F IT: Tel: +39 069 266 91F UK: Tel: +44 151 422 10 <b>1.4 Emergency telephone</b> Customer Service NL: Tel: +31 164 250 10 B: Tel: +32 2 347 0117 F IT: Tel: +39 069 266 91F	00 Fax: + 31 164 266 710 Fax: +32 2 347 1395 Fax: +39 06.927 470 61 100 Fax: +44 151 422 1011 te number: 100 Fax: + 31 164 266 710 Fax: +32 2 347 1395
SECTION 2. Heren	de identification
SECTION 2: Hazar 2.1 Classification of the s Classification according	

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. (Contd. on page 2)

GB

Printing date 03.01.2020

Version: 6

Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)



· Signal word Danger

- · Hazard-determining components of labelling:
- 2-aminoethanol

#### • Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H314 Causes severe skin burns and eye damage.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

*P410+P412* Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.* 

2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

Results of PBT and vPvB assessment

· PBT: Not applicable.

• vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 012119486944-21-xxxx	propane Flam. Gas 1, H220 Press. Gas C, H280	2.5-5%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (< 0.1% butadine)	2.5-5%
CAS: 141-43-5 EINECS: 205-483-3 Reg.nr.: 01-2119486455-28-xxxx	2-aminoethanol Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335 Aquatic Chronic 3, H412	2.5-5%
CAS: 7320-34-5 EINECS: 230-785-7 Reg.nr.: 01-2119489369-18-xxxx	tetrapotassium pyrophosphate	1-2.5%

Ingredients according to Detergents Regulation 648/2004/EC

For the wording of the listed hazard phrases refer to section 16.

ISOPROPYL ALCOHOL

Aliphatic hydrocarbons Phosphates, Nonionic surfactants

## **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

*If skin irritation continues, consult a doctor.* 

≥15 - <30%

≥5 - <15%

<5%

(Contd. of page 1)

Printing date 03.01.2020

Version: 6

Revision: 03.01.2020

(Contd. of page 2)

#### Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

Immediately wash with water and soap and rinse thoroughly. Immediately rinse with water.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor. • After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately. Seek immediate medical advice.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced. • 5.3 Advice for firefighters
- **Protective equipment:** Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

#### **SECTION 6:** Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Use neutralising agent.

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material.
- Keep ignition sources away Do not smoke.
- Keep respiratory protective device available.

*Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.* 

- $\cdot$  7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GB

Printing date 03.01.2020

Version: 6

Revision: 03.01.2020

## Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

67-63-0 propan-2-ol         Oral       DNEL Long term-systemic       26 mg/kg human/day (consumer)         Dermal       DNEL Long term-systemic       319 mg/kg human/day (consumer)         NEL Long term-systemic       888 mg/kg human/day (worker)         Inhalative       DNEL Long term-systemic mg/m3       89 mg/m3 (consumer)         500 mg/m3 (worker)       500 mg/m3 (worker)
WEL (Great Britain)       Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm         106-97-8 butane (< 0.1% butadine) (2.5-5%)         WEL (Great Britain)       Short-term value: 1450 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)         34590-94-8 Dipropylene glycol monomethyl ether (2.5-5%)         WEL (Great Britain)       Long-term value: 308 mg/m³, 50 ppm Sk         IOELV (European Union)       Long-term value: 308 mg/m³, 50 ppm Skin         141-43-5 2-aminoethanot (2.5-5%)         WEL (Great Britain)       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Skin         IOELV (European Union)       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Skin         DNELs       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Skin         DNELs       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Skin         DNEL Long term-systemic       26 mg/kg human/day (consumer)         Oral       DNEL Long term-systemic       319 mg/kg human/day (consumer)         88 mg/kg human/day (worker)       Net Long term-systemic mg/m³       39 mg/m3 (consumer)         90 mg/m3 (worker)       Short-term value: 2.5 mg/m³ (worker)       Short-term value: 2.5 mg/m³, 1 ppm
Ide-97-8 butane (< 0.1% butadine) (2.5-5%)
106-97-8 butane (< 0.1% butadine) (2.5-5%)
Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)34590-94-8 Dipropylene glycol monomethyl ether (2.5-5%)WEL (Great Britian)Long-term value: 308 mg/m³, 50 ppm Sk10ELV (European Union)Long-term value: 308 mg/m³, 50 ppm Skin141-43-5 2-aminoethanot (2.5-5%)WEL (Great Britian)Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk10ELV (European Union)Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk10ELV (European Union)Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk10ELV (European Union)Dometerm value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk00FLEs00FLEs00PNELs00PNELs01NEL Long term-systemic 888 mg/kg human/day (consumer) 888 mg/kg human/day (consumer) 888 mg/kg human/day (worker)PNECSPNECS
WEL (Great Britain)       Long-term value: 308 mg/m³, 50 ppm Sk         IOELV (European Union)       Long-term value: 308 mg/m³, 50 ppm Skin         141-43-5 2-aminoethanol (2.5-5%)         WEL (Great Britain)       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk         IOELV (European Union)       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk         IOELV (European Union)       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Skin         DNELS       5         67-63-0 propan-2-ol       26 mg/kg human/day (consumer)         Oral       DNEL Long term-systemic       26 mg/kg human/day (consumer)         Dermal       DNEL Long term-systemic       319 mg/kg human/day (worker)         Inhalative       DNEL Long term-systemic mg/m³       89 mg/m3 (consumer)         90 mg/m3 (worker)       500 mg/m3 (worker)
Sk       Sk         IOELV (European Union)       Long-term value: 308 mg/m³, 50 ppm Skin         141-43-5 2-aminoethanol (2.5-5%)         WEL (Great Britain)       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk         IOELV (European Union)       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Skin         DNELS       Forg-term value: 2.5 mg/m³, 1 ppm Skin         Oral       DNEL Long term-systemic       26 mg/kg human/day (consumer) 319 mg/kg human/day (consumer)         Dermal       DNEL Long term-systemic mg/m³       888 mg/kg human/day (worker)         Inhalative       DNEL Long term-systemic mg/m³       89 mg/m3 (consumer)         67-63-0 propan-2-ol       89 mg/m3 (worker)
Image: Skin         Image: Im
WEL (Great Britain)       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk         IOELV (European Union)       Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Skin         DNELs       Short-term value: 2.5 mg/m³, 1 ppm Skin         Oral       DNEL Long term-systemic       26 mg/kg human/day (consumer)         Dermal       DNEL Long term-systemic       319 mg/kg human/day (consumer)         Bonel Long term-systemic mg/m³       888 mg/kg human/day (worker)         Inhalative       DNEL Long term-systemic mg/m³       89 mg/m3 (consumer)         500 mg/m3 (worker)       500 mg/m3 (worker)
IOELV (European Union)Long-term value: 2.5 mg/m³, 1 ppm SkIOELV (European Union)Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm SkinDNELsCong-term value: 2.5 mg/m³, 1 ppm Skin0ralDNEL Long term-systemic26 mg/kg human/day (consumer)OralDNEL Long term-systemic319 mg/kg human/day (consumer)BermalDNEL Long term-systemic mg/m³88 mg/kg human/day (worker)InhalativeDNEL Long term-systemic mg/m³89 mg/m3 (consumer)500 mg/m3 (worker)500 mg/m3 (worker)
Long-term value: 2.5 mg/m³, 1 ppm         Skin         DNELs         67-63-0 propan-2-ol         Oral       DNEL Long term-systemic         Dermal       DNEL Long term-systemic         Joner       319 mg/kg human/day (consumer)         Box       888 mg/kg human/day (worker)         Inhalative       DNEL Long term-systemic mg/m3         PNECs       500 mg/m3 (worker)         67-63-0 propan-2-ol
67-63-0 propan-2-ol         Oral       DNEL Long term-systemic       26 mg/kg human/day (consumer)         Dermal       DNEL Long term-systemic       319 mg/kg human/day (consumer)         Inhalative       DNEL Long term-systemic mg/m3       89 mg/m3 (consumer)         500 mg/m3 (worker)       500 mg/m3 (worker)         PNECs
Oral       DNEL Long term-systemic       26 mg/kg human/day (consumer)         Dermal       DNEL Long term-systemic       319 mg/kg human/day (consumer)         Inhalative       DNEL Long term-systemic mg/m3       888 mg/kg human/day (worker)         Inhalative       DNEL Long term-systemic mg/m3       89 mg/m3 (consumer)         500 mg/m3 (worker)       500 mg/m3 (worker)         67-63-0 propan-2-ol
Dermal       DNEL Long term-systemic       319 mg/kg human/day (consumer)         Inhalative       DNEL Long term-systemic mg/m3       888 mg/kg human/day (worker)         89 mg/m3 (consumer)       500 mg/m3 (worker)         67-63-0 propan-2-ol       500 mg/m3 (worker)
Inhalative       DNEL Long term-systemic mg/m3       888 mg/kg human/day (worker)         89 mg/m3 (consumer)       500 mg/m3 (worker)         • PNECs       67-63-0 propan-2-ol
Inhalative       DNEL Long term-systemic mg/m3       89 mg/m3 (consumer)         500 mg/m3 (worker)         PNECs         67-63-0 propan-2-ol
500 mg/m3 (worker) PNECs 67-63-0 propan-2-ol
PNECs 67-63-0 propan-2-ol
67-63-0 propan-2-ol
PNEC Freshwater mg/L 140.9 mg/L
PNEC Marinewater mg/L 140.9 mg/L
PNEC Freshwater sediment 552 mg/Kg
PNEC Marine water sediment 552 mg/Kg
PNEC Intermittent release 140.9
PNEC Soil 28 mg/Kg
Additional information: The lists valid during the making were used as basis.
8.2 Exposure controls Personal protective equipment: General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- **Respiratory protection:** Not required.
- Protection of hands:



Protective gloves

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 03.01.2020

Version: 6

Revision: 03.01.2020

(Contd. of page 4)

## Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. • Not suitable are gloves made of the following materials: Strong material gloves

• Eye protection:



Tightly sealed goggles

# **SECTION 9: Physical and chemical properties**

General Information	
Appearance: Form:	Aerosol
	Colourless
Colour: Odour:	Colouriess Characteristic
Odour: Odour threshold:	Not determined.
pH-value at 20 °C:	11.5
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. •• 82 °C
Flash point:	<0 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	425 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	2 Vol %
Upper:	12 Vol %
Vapour pressure at 20 °C:	42 hPa
Density at 20 °C:	$0.95 \text{ g/cm}^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	24.5 %
EU-VOC:	261.2 g/l
EU-VOC	27.50 %
Swiss VOC:	27.50 %
Solids content:	1.0 %
9.2 Other information	No further relevant information available.

(Contd. on page 6)

Printing date 03.01.2020

Version: 6

Revision: 03.01.2020

#### Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

(Contd. of page 5)

### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	values relevar	nt for classification:
67-63-0 pr	opan-2-ol	
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	6,290 mg/kg (rab)
Inhalative	LC50 / 4 h	46-73 mg/l (Rat)
	LC50/ 8 h	12,000-19,000 mg/m3 (Rat)
	LC50 / 96 h	9,640 mg/ltr (fish)
		>1,400 mg/ltr (Lepomus gobbosus (Zonnebaars))
		6,550 mg/ltr (Pimephales promelas)
	EC50 / 24 h	>1,000 mg/ltr (Daphnia magna (water flea))
	EC 50 / 48 h	2,285-13,299 mg/ltr (Daphnia magna (water flea))
141-43-5 2	2-aminoethan	ol
Oral	LD50	1,720 mg/kg (Rat)
Dermal	LD50	1,018 mg/kg (Rabbit)
	LC50 / 48 h	>200 mg/ltr (Lepomus gobbosus (Zonnebaars))
	EC 50 / 48 h	>100 mg/ltr (Daphnia magna (water flea))
7320-34-5	tetrapotassiu	m pyrophosphate
Oral	LD50	>2,000 mg/kg (Mouse)
		>2,000 mg/kg (Rat)
		>7,940 mg/kg (Rabbit)
	LC50 / 48 h	>100 mg/ltr (Daphnia magna (water flea))
	LC50 / 96 h	>100 mg/ltr (Oncorhynchus mykiss (Rainbow trout))
	ritant effect:	
	sion/irritation	
	vere skin burn: 2 <b>e damage/irri</b>	s and eye damage. Itation
	ious eye dama	
		itisation Based on available data, the classification criteria are not met.

*CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)* 

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

• *Reproductive toxicity Based on available data, the classification criteria are not met.* 

· STOT-single exposure Based on available data, the classification criteria are not met.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

• 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

GB

Printing date 03.01.2020

Version: 6

Revision: 03.01.2020

(Contd. of page 6)

#### Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

#### · Additional ecological information:

• General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations
- · Uncleaned packaging:
- · Recommendation: Disposal in accordance with administrative provisions

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class Label	2 5F Gases. 2.1
IMDG, IATA	2.1
Class Label	2.1 2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code Segregation Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 excep for division 1.4. For AEROSOLS with a capacity above 1 litre:

Printing date 03.01.2020

Version: 6

Revision: 03.01.2020

#### Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

	(Contd. of pag
	Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex the IBC Code	II of Marpol and Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities $(\tilde{E}Q)$	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{EQ})$	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg. (ÉC) n. 1272/2008 - CLP; Reg. (EC) n. 1907/2006 – Reach; Reg. (EC) n. 2015/830 annex II of REACH; Reg. (EC) n. 648/04 (Detergents); Reg. (EC) n. 528/12 (Biocides BPR); Reg. (EC) n. 1223/2009 (Cosmetics); Dir. 06/08 ADR – RID - IMDG - IATA; Dir. 47/08 (Aerosols); Dir. 12/18 (Seveso III); Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

• Technical instructions (air):

 Class
 Share in %

 NK
 25-50

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water. • 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

(Contd. on page 9)

GB

Printing date 03.01.2020

Version: 6

Revision: 03.01.2020

# Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

	(Contd. of page 8)
H336 May cause drowsiness or dizziness.	
H412 Harmful to aquatic life with long lasting effects.	
Department issuing SDS:	
Customer Service	
NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710	
<i>B: Tel:</i> +32 2 347 0117 Fax: +32 2 347 1395	
IT: Tel: +39 069 266 91Fax: +39 06.927 470 61	
UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011	
Contact:	
Customer Service	
<i>NL: Tel:</i> + 31 164 250 100 <i>Fax:</i> + 31 164 266 710	
<i>B</i> : <i>Tel</i> : +32 2 347 0117 Fax: +32 2 347 1395	
IT: Tel: +39 069 266 91Fax: +39 06.927 470 61	
UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concernin,	g the International Transport of
Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Internat	ional Carriage of Dangerous Goods
by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)	
VOC: Lenkingsabgabe all fulchingen organischen Verbindungen, Schweiz (Swiss Ordinance on Volatile organic compounds) VOC: Volatile Organic Compounds (USA, EU)	
DNEL: Derived No-Effect Level (REACH)	
PNEC: Predicted No-Effect Concentration (REACH)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1: Flammable gases – Category 1	
Aerosol 1: Aerosols – Category 1	
Press. Gas C: Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Acute Tox. 4: Acute toxicity - oral – Category 4	
Skin Corr. 1B: Skin corrosion/irritation – Category 1B	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Junit 2: Serious and damage/eye irritation – Category 2	
<i>Eye Irrit. 2: Serious eye damage/eye irritation – Category 2</i> <i>STOT SE 3: Specific target organ toxicity (single exposure) – Category 3</i>	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* Data compared to the previous version altered.	
Dum comparen lo ine previous version uneren.	G

(Contd. on page 10)

Printing date 03.01.2020

Version: 6

Revision: 03.01.2020

## Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

(Contd. of page 9)

Annex: Ex	posure scenario
Short title of	he exposure scenario
For the finish	
	SE NEW (Listed NSF A8: n° 152106)
	SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
	ory PC35 Washing and cleaning products (including solvent based products)
Process categ	
	strial spraying
	n industrial spraying
	f the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Shee
Conditions of	
	frequency 5 workdays/week.
Physical para	
Physical state	
	t of the substance in the mixture The substance is main component.
	per time or activity According to directions for use.
	onal conditions
	onal conditions affecting environmental exposure No special measures required.
	onal conditions affecting worker exposure
Avoid contact	
	onary measures against static discharge.
	m sources of ignition - No smoking.
Avoid contact	
	onal conditions affecting consumer exposure Keep out of the reach of children.
	onal conditions affecting consumer exposure during the use of the product Not applicable.
	nent measures
Worker prote	
	al protective measures No special measures required.
	tective measures
	sion-proof electrical equipment.
	itable extractors are available on processing machines
	ective measures
Avoid contact	
Tightly sealed	
Avoid contact	
Protective glo	
	consumer protection
Ensure adequ	
	p and out of the reach of children.
	al protection measures
Water	
	asures required.
*	or to the introduction of wastewater into wastewater treatment plants a neutralisation is required.
Disposal mea	
	cordance with administrative provisions
	aste is collected and contained.
	aste is conected and contained. edures Must not be disposed together with household garbage. Do not allow product to reach sewage system.
	rtially emptied and uncleaned packaging
Exposure esti	
	t relevant for this Exposure Scenario.
Guidance for	downstream users No further relevant information available.