Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: DRY GRAPHITE II
- · Article number: 10640001
- · UFI: DJ90-404G-000T-3Y8R
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Life cycle stages

PW Widespread use by professional workers

IS Use at industrial Sites

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category PC24 Lubricants, greases, release products
- · Process category

PROC7 Industrial spraying PROC11 Non industrial spraying

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

ZEP ITALIA SRL

Piazzale Luigi Cadorna, 2

20123 Milano (MI) - Italy;

Via Nettunense Km. 25.000

04011 Aprilia (LT) - Italy

T: +39.06.926691

F: +39.06.92747061

@: tecnico@zepeurope.com

Sito: www.zep.it

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117

Fax:(NL) + 31 164 266 710 (B) + 32 2 347 1395

@: info@zepbenelux.com

Distribuited in the UK by:

ZEP UK Ltd

Tanhouse Lane

Widnes Cheshire, WA8 0RD

United Kingdom

Tel: +44 (0)151 422 1000

Fax: +44 (0)151 422 1011

@: info@zep.co.uk

web: www.zep.co.uk

· Further information obtainable from:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· 1.4 Emergency telephone number: NHS +44 0845 46 47 (England or Wales); +44 08454 24 24 24 (Scotland)

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

  (Contd. on page 2)

EU

(Contd. of page 1)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

Trade name: DRY GRAPHITE II

#### · Hazard pictograms





· Signal word Danger

### · Hazard-determining components of labelling:

propan-2-ol butanol

1-methoxy-2-propanol

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · 2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

· **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 106-97-8	butane	25-50%
EINECS: 203-448-7	◆ Flam. Gas 1A, H220	
Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	Press. Gas (Comp.), H280	
CAS: 109-87-5	dimethoxymethane	25-50%
EINECS: 203-714-2 Reg.nr.: 01-2119664781-31-XXXX	<b>♦</b> Flam. Liq. 2, H225	20 00,0
CAS: 67-63-0	propan-2-ol	10-25%
EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 74-98-6	propane	5-10%
EINECS: 200-827-9	♠ Flam. Gas 1A, H220	
Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	Press. Gas (Comp.), H280	
CAS: 75-28-5	and isobutane	5-10%
EINECS: 200-857-2	♦ Flam. Gas 1A, H220	
Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	Press. Gas (Comp.), H280	
CAS: 107-98-2	1-methoxy-2-propanol	0.1-1%
EINECS: 203-539-1	Flam. Liq. 3, H226	
Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35-xxxx	♦ STOT SĒ 3, H336	

Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

Trade name: DRY GRAPHITE II

(Contd. of page 2)

### SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air; consult doctor in case of complaints.

Seek medical treatment.

- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing:

Seek immediate medical advice.

Do not induce vomiting; call for medical help immediately.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Carbon dioxide

Alcohol resistant foam

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Wear self-contained respiratory protective device.

· Additional information Cool endangered receptacles with water spray.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

(Contd. on page 4)

Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

Trade name: DRY GRAPHITE II

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:

#### CAS: 107-98-2 1-methoxy-2-propanol

IOELV Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

DNEL Long term-systemic

· DNELs

## CAS: 67-63-0 propan-2-ol

Dermal	DNEL Long term-systemic	319 mg/kg human/day (consumer)
		888 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m3	89 mg/m3 (consumer)
		500 mg/m3 (worker)
CAS: 107-	98-2 1-methoxy-2-propanol	
Oral	DNEL Long term-systemic	3.3 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	18.1 mg/kg human/day (consumer)
		50.6 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m3	43.9 mg/m3 (consumer)
		369 mg/m3 (worker)

553.5 mg/m3 (worker)

26 mg/kg human/day (consumer)

#### · PNECs

#### CAS: 67-63-0 propan-2-ol

PNEC Freshwater mg/L	140.9 mg/L
PNEC Marinewater mg/L	140.9 mg/L 140.9 mg/L 552 mg/Kg 552 mg/Kg
PNEC Freshwater sediment	552 mg/Kg
PNEC Marine water sediment	552 mg/Kg
PNEC Intermittent release	140.9
PNEC Soil	28 mg/Kg

DNEL Acute-local mg/m3

### CAS: 107-98-2 1-methoxy-2-propanol

PNEC Freshwater mg/L	10 mg/L
PNEC Freshwater sediment	10 mg/L 41.6 mg/Kg 4.17 mg/Kg 2.47 mg/Kg
PNEC Marine water sediment	4.17 mg/Kg
PNEC Soil	2.47 mg/Kg
PNEC Sewage treatment Plant mg/L	100 mg/L

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Protection of hands:



Protective gloves

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

*Printing date 31.03.2021 Version: 7 Revision: 31.03.2021* 

Trade name: DRY GRAPHITE II

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- · Not suitable are gloves made of the following materials: Strong material gloves
- · Eye protection:



· Body protection: Use protective suit.

SECTION 9: Physical and chem	icui properties	
9.1 Information on basic physical and c	hemical properties	
· General Information		
Appearance:		
Form:	Aerosol	
Colour:	Characteristic	
Odour: Odour threshold:	Characteristic Not determined.	
pH-value:	Not determined.	
<u> </u>	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range		
Flash point:	-97 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	235 ℃	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
Explosion limits:		
Lower:	1.5 Vol %	
Upper:	8.5 Vol %	
Vapour pressure at 20 °C:	2100 hPa	
Density:	Not determined.	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	90.0 %	
EU-VOC:	93.2 %	
Swiss VOC:	99.10 %	
9.2 Other information	No further relevant information available.	

Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

Trade name: DRY GRAPHITE II

(Contd. of page 5)

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:
ATE (Acute Toxicity Estimates)

Oral	LD50	47,400 mg/kg
Dermal	LD50	120,000 mg/kg

CAS:	<i>67-63-0</i>	pro	pan-2-ol
------	----------------	-----	----------

Oral	LD50	>5,000 mg/kg (Rat)
Dermal		13,900 mg/kg (rab)
		46-73 mg/l (Rat)
	LC50/8 h	12,000-19,000 mg/m3 (Rat)
	EC50 / 24 h	>1,000 mg/ltr (Daphnia magna (water flea

#### CAS: 107-98-2 1-methoxy-2-propanol

Oral	LD50	4,016 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	27,596 mg/l (Rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· 12 1 Toxicity

	12.1 Toxicity	12.1 Toxicily	
	· Aquatic toxicity:		
	CAS: 67-63-0 propa	n-2-ol	
	LC50 / 96 h	9,640 mg/ltr (fish)	
		>1,400 mg/ltr (Lepomus gobbosus (Zonnebaars))	
		6,550 mg/ltr (Pimephales promelas)	
	EC 50 / 48 h	2,285-13,299 mg/ltr (Daphnia magna (water flea))	
CAS: 107-98-2 1-methoxy-2-propanol		ethoxy-2-propanol	
	LC50 / 96 h (static) 6,812 mg/ltr (Leuciscus idus)		
	EC 50 / 48 h (static)	23,300 mg/ltr (Daphnia magna (water flea))	

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 7)

Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

Trade name: DRY GRAPHITE II

(Contd. of page 6)

- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations

· European	· European waste catalogue	
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED	
15 01 00	packaging (including separately collected municipal packaging waste)	
15 01 04	metallic packaging	
20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS	
20 01 00	separately collected fractions (except 15 01)	
20 01 99	other fractions not otherwise specified	
07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES	
07 01 00	wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals	
07 01 04*	other organic solvents, washing liquids and mother liquors	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	

- · Uncleaned packaging:
- · Recommendation: Disposal in accordance with administrative provisions

SECTION 14:	Transport in	formation
-------------	--------------	-----------

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS
· IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class
 · Label
 2 5F Gases.
 2.1

· IMDG, IATA



· Class 2.1 · Label 2.1

(Contd. on page 8)

Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

Trade name: DRY GRAPHITE II

	(Contd. of pag
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Code · Segregation Code	Warning: Gases.  F-D,S-U  SW1 Protected from sources of heat.  SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 exceptor division 1.4.  For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.  For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marp the IBC Code	pol and Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code · IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity 2 D  1L Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg. (EC) n. 1272/2008 - CLP;

Reg. (EC) n. 2015/830 annex II of REACH;

Dir. 06/08 ADR – RID - IMDG - IATA;

Dir. 12/18 (Seveso III);

Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms





GHS02

GHSU

- · Signal word Danger
- · Hazard-determining components of labelling:

propan-2-ol

butanol

 $1\hbox{-}methoxy\hbox{-}2\hbox{-}propanol$ 

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

(Contd. on page 9)

Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

Trade name: DRY GRAPHITE II

(Contd. of page 8)

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment

– Annex II

None of the ingredients is listed.

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	99.1

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing SDS:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Contact:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent

(Contd. on page 10)

Page 10/11

(Contd. of page 9)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

Trade name: DRY GRAPHITE II

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
WELL: The highest acceptable concentration
IOELV: Indicative occupational exposure limit values
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Eve Irrit. 2: Serious eve damase/eve irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

(Contd. on page 11)

Printing date 31.03.2021 Version: 7 Revision: 31.03.2021

Trade name: DRY GRAPHITE II

(Contd. of page 10)

### Annex: Exposure scenario

- · Short title of the exposure scenario For the finished product.
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC24 Lubricants, greases, release products
- · Process category

PROC7 Industrial spraying PROC11 Non industrial spraying

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Aerosol
- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity According to directions for use.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- · Other operational conditions affecting consumer exposure Keep out of the reach of children.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures Provide explosion-proof electrical equipment.
- Personal protective measures The usual precautionary measures are to be adhered to when handling chemicals.
- · Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

- · Environmental protection measures
- · Water No special measures required.
- · Disposal measures

Disposal in accordance with administrative provisions

Ensure that waste is collected and contained.

- Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.